



3830

**Sandflex® Bi-Metal Holesaws for
Metal/Wood Boards 14 mm-210
mm**



PRODUCT DETAILS

- Sandflex® bi-metal holesaws work excellently in most materials such as wood, plastics, non ferrous and ferrous steel including stainless steel
- Bi-metal construction with 8% cobalt for increased wear resistance
- Fit all power drills, both stationary and portable
- Knockout holes allow easy removal of cores
- Cutting depth max 38 mm (1 1/2")
- 4/6 teeth per inch
- Max. holesize = nominal holesaw size +1.5 mm./- 0.0
- All -C holesaws are packed in a nice self-service packing with an instruction leaflet that also works as a tooth protector
- Designed for professional use
- Bi-metal construction with 8% cobalt for increased wear resistance
- Holesaws with standard attachment to fit a wide range of arbors
- High quality in terms of precision, durability and versatility
- No matter what you are cutting through, we have the holesaws and arbors to tackle the job, time after time
- Engineered to improve productivity and craftsmanship from the design of the cutting edges to the technologies used to produce the holesaws

Follow the Fish!



PRODUCT ATTRIBUTES

Product		
3830-14-C	14 mm	30 g
3830-16-C	16 mm	35 g
3830-17-C	17 mm	40 g
3830-19-C	19 mm	43 g
3830-20-C	20 mm	45 g
3830-21-C	21 mm	50 g
3830-22-C	22 mm	52 g
3830-24-C	24 mm	55 g
3830-25-C	25 mm	58 g
3830-27-C	27 mm	60 g
3830-29-C	29 mm	65 g
3830-30-C	30 mm	65 g
3830-32-C	32 mm	70 g
3830-33-C	33 mm	75 g
3830-35-C	35 mm	75 g
3830-37-C	37 mm	80 g
3830-38-C	38 mm	85 g
3830-40-C	40 mm	90 g
3830-41-C	41 mm	90 g
3830-43-C	43 mm	100 g
3830-44-C	44 mm	100 g
3830-46-C	46 mm	115 g
3830-48-C	48 mm	120 g
3830-50-C	50 mm	130 g
3830-51-C	51 mm	135 g
3830-52-C	52 mm	140 g
3830-54-C	54 mm	150 g
3830-55-C	55 mm	155 g
3830-56-C	56 mm	160 g
3830-57-C	57 mm	165 g
3830-59-C	59 mm	170 g
3830-60-C	60 mm	177 g
3830-64-C	64 mm	200 g
3830-65-C	65 mm	205 g
3830-67-C	67 mm	215 g
3830-68-C	68 mm	220 g
3830-70-C	70 mm	230 g
3830-73-C	73 mm	245 g
3830-76-C	76 mm	260 g
3830-79-C	79 mm	270 g
3830-83-C	83 mm	305 g
3830-86-C	86 mm	325 g
3830-89-C	89 mm	345 g
3830-92-C	92 mm	355 g
3830-95-C	95 mm	385 g
3830-98-C	98 mm	400 g
3830-102-C	102 mm	425 g
3830-105-C	105 mm	445 g
3830-109-C	109 mm	475 g
3830-111-C	111 mm	500 g
3830-114-C	114 mm	540 g
3830-121-C	121 mm	590 g
3830-127-C	127 mm	645 g
3830-133-C	133 mm	720 g
3830-140-C	140 mm	770 g
3830-146-C	146 mm	815 g
3830-152-C	152 mm	885 g
3830-14-VIP	14 mm	30 g
3830-16-VIP	16 mm	35 g
3830-17-VIP	17 mm	40 g
3830-19-VIP	19 mm	43 g
3830-20-VIP	20 mm	45 g
3830-21-VIP	21 mm	50 g
3830-22-VIP	22 mm	52 g
3830-24-VIP	24 mm	55 g
3830-25-VIP	25 mm	58 g
3830-27-VIP	27 mm	60 g
3830-29-VIP	29 mm	65 g
3830-30-VIP	30 mm	65 g
3830-32-VIP	32 mm	70 g
3830-33-VIP	33 mm	75 g
3830-35-VIP	35 mm	75 g
3830-37-VIP	37 mm	80 g
3830-38-VIP	38 mm	85 g
3830-40-VIP	40 mm	90 g
3830-41-VIP	41 mm	90 g
3830-43-VIP	43 mm	100 g
3830-44-VIP	44 mm	100 g
3830-46-VIP	46 mm	115 g
3830-48-VIP	48 mm	120 g
3830-50-VIP	50 mm	130 g
3830-51-VIP	51 mm	135 g
3830-52-VIP	52 mm	140 g
3830-54-VIP	54 mm	150 g
3830-55-VIP	55 mm	155 g
3830-56-VIP	56 mm	160 g
3830-57-VIP	57 mm	165 g
3830-59-VIP	59 mm	170 g
3830-60-VIP	60 mm	177 g
3830-62-VIP	62 mm	190 g
3830-64-VIP	64 mm	200 g
3830-65-VIP	65 mm	205 g
3830-67-VIP	67 mm	215 g
3830-68-VIP	68 mm	220 g
3830-70-VIP	70 mm	245 g
3830-73-VIP	73 mm	270 g
3830-76-VIP	76 mm	285 g
3830-79-VIP	79 mm	295 g
3830-83-VIP	83 mm	330 g
3830-86-VIP	86 mm	350 g
3830-89-VIP	89 mm	370 g
3830-92-VIP	92 mm	380 g
3830-95-VIP	95 mm	410 g
3830-98-VIP	98 mm	430 g
3830-102-VIP	102 mm	455 g
3830-105-VIP	105 mm	475 g
3830-109-VIP	109 mm	500 g
3830-111-VIP	111 mm	530 g
3830-114-VIP	114 mm	570 g
3830-121-VIP	121 mm	635 g
3830-127-VIP	127 mm	690 g
3830-133-VIP	133 mm	765 g
3830-140-VIP	140 mm	815 g
3830-146-VIP	146 mm	860 g
3830-152-VIP	152 mm	930 g
3830-168	168 mm	1315 g
3830-177-HIGH	177 mm	1570 g
3830-210	210 mm	1900 g

Follow the Fish!



Contact: info@bahco.com / www.bahco.com